


JIS-10K
球狀石墨鑄鐵球型閥
Ductile Iron Globe Valve
螺紋口
Screwed
TG-16K (SUS Disc)
TT-16K (Teflon Disc)
標稱壓力Working pressure marking 16 kgf/cm²

120°C以下之靜流水

Non shock water under 120°C 14 kgf/cm²

220°C以下之蒸汽、氣體、瓦斯、油、脈動水

Steam, Air, Gas, Oil, Pulse stream under 220°C 10 kgf/cm²

※Teflon墊片最高使用溫度180°C (356°F)

測試壓力Test Pressure


閥體 Body 24 kgf/cm² (Hydrostatic)閥座 Seat 15 kgf/cm² (Hydrostatic)6 kgf/cm² (Air)

Parts and materials list

| | |
|------------------|-----------------------|
| 閥體 Body | FCD450 |
| 閥蓋 Bonnet | FCD450 |
| 閥桿 Stem | SUS410 |
| 閥門 Disc | SUS410/PTFE+15%G.F.T. |
| 閥座 Seat Ring | SUS410 |
| 迫緊 Packing | Graphite |
| 迫緊螺帽 Packing Nut | FCD450 |
| 把手 Handwheel | FCD450 |
| 銘牌 Name Plate | Aluminum |

• Connection Screwed End (P.T.)

| Size | mm | 10 | 15 | 20 | 25 | 32 | 40 | 50 |
|---------|------|-----|-----|-----|-----|-------|-------|-----|
| | inch | 3/8 | 1/2 | 3/4 | 1 | 1 1/4 | 1 1/2 | 2 |
| L | | 60 | 65 | 80 | 90 | 105 | 120 | 140 |
| H(open) | | 98 | 98 | 112 | 130 | 150 | 165 | 190 |
| D1 | | 70 | 70 | 80 | 90 | 100 | 120 | 140 |

JIS-10K
球狀石墨鑄鐵球型閥
Ductile Iron Globe Valve
法蘭口
Flanged
TGF-16K (SUS Disc)
TTF-16K (Teflon Disc)
標稱壓力Working pressure marking 16 kgf/cm²

120°C以下之靜流水

Non shock water under 120°C 14 kgf/cm²

220°C以下之蒸汽、氣體、瓦斯、油、脈動水

Steam, Air, Gas, Oil, Pulse stream under 220°C 12 kgf/cm²

300°C以下之蒸汽、氣體、瓦斯、油、脈動水

Steam, Air, Gas, Oil, Pulse stream under 300°C 10 kgf/cm²

※Teflon墊片最高使用溫度180°C (356°F)

測試壓力Test Pressure


閥體 Body 24 kgf/cm² (Hydrostatic)閥座 Seat 15 kgf/cm² (Hydrostatic)6 kgf/cm² (Air)

Parts and materials list

| | |
|------------------|-----------------------|
| 閥體 Body | FCD450 |
| 閥蓋 Bonnet | FCD450 |
| 閥桿 Stem | SUS410 |
| 閥門 Disc | SUS410/PTFE+15%G.F.T. |
| 閥座 Seat Ring | SUS410 |
| 連結螺帽 Lock Nut | FCD450 |
| 墊片 Gasket | Non Asbestos |
| 迫緊 Packing | Graphite |
| 迫緊螺帽 Packing Nut | FCD450 |
| 把手 Handwheel | FCD450 |
| 銘牌 Name Plate | Aluminum |

• Connection Flanged End (R.F.)

| Size | mm | 15 | 20 | 25 | 32 | 40 | 50 |
|---------|------|-----|-----|-----|-------|-------|-----|
| | inch | 1/2 | 3/4 | 1 | 1 1/4 | 1 1/2 | 2 |
| L | | 108 | 117 | 127 | 140 | 165 | 203 |
| H(open) | | 140 | 160 | 170 | 180 | 204 | 235 |
| D1 | | 80 | 100 | 100 | 120 | 140 | 140 |

JIS-20K
球狀石墨鑄鐵球型閥
Ductile Iron Globe Valve
螺紋口
Screwed
TG-20K (SUS Disc)
TT-20K (Teflon Disc)


標稱壓力Working pressure marking 20 kgf/cm²
 120°C以下之靜流水
 Non shock water under 120°C 28 kgf/cm²
 220°C以下之蒸汽、氣體、瓦斯、油、脈動水
 Steam, Air, Gas, Oil, Pulse stream under 220°C 25 kgf/cm²
 300°C以下之蒸汽、氣體、瓦斯、油、脈動水
 Steam, Air, Gas, Oil, Pulse stream under 300°C 23 kgf/cm²
 350°C以下之蒸汽、氣體、瓦斯、油、脈動水
 Steam, Air, Gas, Oil, Pulse stream under 350°C 20 kgf/cm²
 ※Teflon墊片最高使用溫度180°C (356°F)

測試壓力Test Pressure


| | |
|---------|--------------------------------------|
| 閥體 Body | 44 kgf/cm ² (Hydrostatic) |
| 閥座 Seat | 32 kgf/cm ² (Hydrostatic) |
| | 6 kgf/cm ² (Air) |

Parts and materials list

| | |
|------------------|-----------------------|
| 閥體 Body | FCD450 |
| 閥蓋 Bonnet | FCD450 |
| 閥桿 Stem | SUS410 |
| 閥門 Disc | SUS410/PTFE+15%G.F.T. |
| 閥座 Seat Ring | SUS410 |
| 連結螺帽 Lock Nut | FCD450 |
| 墊片 Gasket | Non Asbestos |
| 迫緊 Packing | Graphite |
| 迫緊螺帽 Packing Nut | FCD450 |
| 把手 Handwheel | FCD450 |

• Connection.....Screwed End (P.T.)

| Size | mm | 15 | 20 | 25 | 32 | 40 | 50 |
|---------|------|-----|-----|-----|-----|-----|-----|
| | inch | ½ | ¾ | 1 | 1¼ | 1½ | 2 |
| L | | 75 | 90 | 105 | 120 | 135 | 160 |
| H(open) | | 140 | 155 | 165 | 175 | 200 | 225 |
| D1 | | 80 | 100 | 120 | 120 | 140 | 180 |

JIS-20K
球狀石墨鑄鐵球型閥
Ductile Iron Globe Valve
法蘭口
Flanged
TGF-20K (SUS Disc)
TTF-20K (Teflon Disc)


標稱壓力Working pressure marking 20 kgf/cm²
 120°C以下之靜流水
 Non shock water under 120°C 28 kgf/cm²
 220°C以下之蒸汽、氣體、瓦斯、油、脈動水
 Steam, Air, Gas, Oil, Pulse stream under 220°C 25 kgf/cm²
 300°C以下之蒸汽、氣體、瓦斯、油、脈動水
 Steam, Air, Gas, Oil, Pulse stream under 300°C 23 kgf/cm²
 350°C以下之蒸汽、氣體、瓦斯、油、脈動水
 Steam, Air, Gas, Oil, Pulse stream under 350°C 20 kgf/cm²
 ※Teflon墊片最高使用溫度180°C (356°F)

測試壓力Test Pressure


| | |
|---------|--------------------------------------|
| 閥體 Body | 44 kgf/cm ² (Hydrostatic) |
| 閥座 Seat | 32 kgf/cm ² (Hydrostatic) |
| | 6 kgf/cm ² (Air) |

Parts and materials list

| | |
|------------------|-----------------------|
| 閥體 Body | FCD450 |
| 閥蓋 Bonnet | FCD450 |
| 閥桿 Stem | SUS410 |
| 閥門 Disc | SUS410/PTFE+15%G.F.T. |
| 閥座 Seat Ring | SUS410 |
| 連結螺帽 Lock Nut | FCD450 |
| 墊片 Gasket | Non Asbestos |
| 迫緊 Packing | Graphite |
| 迫緊螺帽 Packing Nut | FCD450 |
| 把手 Handwheel | FCD450 |

• Connection.....Flanged End (R.F.)

| Size | mm | 15 | 20 | 25 | 32 | 40 | 50 |
|---------|------|-----|-----|-----|-----|-----|-----|
| | inch | ½ | ¾ | 1 | 1¼ | 1½ | 2 |
| L | | 110 | 120 | 130 | 160 | 180 | 230 |
| H(open) | | 140 | 160 | 165 | 175 | 205 | 225 |
| D1 | | 80 | 100 | 120 | 120 | 140 | 180 |

JIS-10K
球狀石墨鑄鐵球型閥
Ductile Iron Globe Valve
法蘭口
Flanged
TGF-16K (SUS Disc)
TTF-16K (Teflon Disc)


標稱壓力 Working pressure marking 16 kgf/cm²
 120°C 以下之靜流水 Non shock water under 120°C 16 kgf/cm²
 220°C 以下之蒸汽、氣體、瓦斯、油、脈動水 Steam, Air, Gas, Oil, Pulse stream under 220°C 12 kgf/cm²
 300°C 以下之蒸汽、氣體、瓦斯、油、脈動水 Steam, Air, Gas, Oil, Pulse stream under 300°C 10 kgf/cm²
 ※Teflon墊片最高使用溫度180°C (356°F)

測試壓力 Test Pressure


| | |
|---------|--------------------------------------|
| 閥體 Body | 24 kgf/cm ² (Hydrostatic) |
| 閥座 Seat | 15 kgf/cm ² (Hydrostatic) |
| | 6 kgf/cm ² (Air) |

Parts and materials list

| | |
|------------------|-----------------------|
| 閥 體 Body | FCD450 |
| 閥 蓋 Bonnet | FCD450 |
| 閥 桿 Stem | SUS410 |
| 閥 門 Disc | SUS410/PTFE+15%G.F.T. |
| 閥 座 Seat Ring | SUS410 |
| 墊 片 Gasket | Non Asbestos |
| 迫 緊 Packing | Graphite |
| 迫緊螺帽 Packing Nut | FCD450 |
| 把 手 Handwheel | FCD450 |
| 銘 牌 Name Plate | Aluminum |

• Connection Flanged End (R.F.)

| Size | mm | 65 | 80 | 100 | 125 | 150 | 200 |
|---------|------|-----|-----|-----|-----|-----|-----|
| | inch | 2½ | 3 | 4 | 5 | 6 | 8 |
| L | | 216 | 241 | 292 | 356 | 406 | 495 |
| H(open) | | 330 | 385 | 420 | 485 | 485 | 590 |
| D1 | | 230 | 230 | 280 | 340 | 340 | 400 |

JIS-16K
球狀石墨鑄鐵由任式逆止閥
Ductile Iron Union Check Valve
螺紋口
Screwed
TUC-16K

TUC-16K

標稱壓力 Working pressure marking 16 kgf/cm²
 120°C 以下之靜流水 Non shock water under 120°C 16 kgf/cm²
 220°C 以下之蒸汽、氣體、瓦斯、油、脈動水 Steam, Air, Gas, Oil, Pulse stream under 220°C 12 kgf/cm²

測試壓力 Test Pressure

| | |
|---------|--------------------------------------|
| 閥體 Body | 24 kgf/cm ² (Hydrostatic) |
| 閥座 Seat | 15 kgf/cm ² (Hydrostatic) |
| | 6 kgf/cm ² (Air) |

Parts and materials list

| | |
|---------------|--------|
| 閥 體 Body | FCD450 |
| 閥 蓋 Cap | FCD450 |
| 閥 門 Disc | SUS410 |
| 閥 座 Seat Ring | SUS410 |
| 彈 簧 Spring | SUS304 |
| 襯 套 Sleeve | B62 |

• Connection Screwed End (P.T.)

| Size | mm | 15 | 20 | 25 | 32 | 40 | 50 |
|------|------|----|----|----|----|-----|-----|
| | inch | ½ | ¾ | 1 | 1¼ | 1½ | 2 |
| H | | 60 | 70 | 80 | 90 | 100 | 110 |
| D1 | | 41 | 48 | 56 | 72 | 86 | 102 |