



### >>RP-IP2105

#### 4-P Broadband Router

This router is a 4-port Cable/DSL Broadband Router. It provides you an easy and stable way to share your Cable/DSL high speed Internet connection. The built-in NAT technology can act as a firewall to protect your internal network against outside hackers. The 4-port Broadband Router is compatible with most popular operating systems, such as Windows, Linux, Macintosh, etc.

### FEATURES

- Integrates with 4 ports Fast Ethernet switch: 10/100Mbps MDI/MDIX auto-sensing
- Provides 10/100Mbps WAN interface to connect with DSL or cable modem for broadband Internet access
- Supports different Internet connecting modes: PPPoE, DHCP Client and Static IP PPTP
- Built-in NAT (Network Address Transfer) technology acts as a firewall to protect internal sources against outside hackers
- Supports UPnP, Windows XP can find the Router in the network automatically
- Simple, intelligent, web-based management and configuration interface
- Supports DHCP server to retrieve TCP/IP settings automatically from the Router
- Supports virtual server which makes LAN services (such as FTP, WWW, TELNET, DNS, etc) to be accessible to the Internet users

### SPECIFICATION

<b>Standards</b>	<ul style="list-style-type: none"><li>• IEEE802.3 10Base-T, IEEE802.3u 100Base-TX</li></ul>
<b>Interface</b>	<ul style="list-style-type: none"><li>• 4-P * LAN, 1-P * WAN</li></ul>
<b>Management</b>	<ul style="list-style-type: none"><li>• web-based</li></ul>
<b>WAN Type</b>	<ul style="list-style-type: none"><li>• Static IP Address</li><li>• Dynamic IP Address (DHCP Client)</li><li>• PPPoE</li><li>• PPTP</li></ul>
<b>Connection Scheme</b>	<ul style="list-style-type: none"><li>• Connect on Demand/Auto-Disconnect</li><li>• Manually Connect/Disconnect</li><li>• Auto Reconnect</li></ul>
<b>NAT Function</b>	<ul style="list-style-type: none"><li>• One-to-Many NAT</li><li>• One-to-One NAT</li><li>• Virtual Server</li><li>• DMZ Host</li></ul>
<b>Access Control</b>	<ul style="list-style-type: none"><li>• MAC-level Access Control</li><li>• Domain Access Control</li></ul>
<b>Event Logging</b>	<ul style="list-style-type: none"><li>• On-web logging</li><li>• Syslog supported</li></ul>
<b>LED Indicators</b>	<ul style="list-style-type: none"><li>• System, Link/Activity</li></ul>
<b>Power Supply</b>	<ul style="list-style-type: none"><li>• External power Adapter DC 9V 500mA</li></ul>
<b>Environment</b>	<ul style="list-style-type: none"><li>• Operating Temperature: 0°C to 50°C</li><li>• Operating Humidity: 20% to 95 % (Non-Condensing)</li></ul>
<b>Dimension</b>	<ul style="list-style-type: none"><li>• 160 * 83 * 26mm</li></ul>
<b>Certifications</b>	<ul style="list-style-type: none"><li>• FCC, CE</li></ul>

### Ordering information

RP-IP2105      4-P Broadband Router